Blood Bank Refrigerator LX4000BBR

Email: info@labdex.com **website:** www.labdex.com

Description

Blood Bank Refrigerator LX4000BBR is an upright type made up of color sprayed steel (outside) and stainless steel material (inside). It is designed by keeping in mind strict requirements for storage of blood and blood components. It is a microprocessor-based temperature controller with digital display allows user to maintain temperature up to 4 ±1 °C.

Specifications

Capacity	108 L
Bloodbags (450ml)	66
Shelf/drawer	Shelves/2
Cooling method	Forced air cooling
Defrost	Auto
Refrigerant	R134a
Noise	50 (db)
Ambient temperature	10~32 ℃
Temperature range	4±1 ℃
Compressor	EMBRACO/1
Sensor type	NTC
Temperature controller	Microprocessor
Display	Digital display
Inside material	Stainless steel
Outside material	Color sprayed steel
Insulation	PURF
Power consumption	1.95 (kWh/24h)
Power	175 W
Current	1A

Voltage/Frequency	220V/50Hz
Interior size (W x D x H)	432 x 462 x 478 mm
Exterior size (W x D x H)	540 x 630 x 1030 mm
Package size (W x D x H)	700 x 590 x 1200 mm
Net weight	80 kgs
Gross weight	100 kgs

Features

- Designed with individual transparent inner door
- Micro-processor controlled function with digital display
- Designed with forced air cooling system
- It has two shelves with shelves height adjustable function
- 3 standard locks with keys for 3 doors
- LED interior light
- It has various type of alarm function such as High/low temperature, Power failure, Thermostat failure, Power failure backup system and Door ajar
- Auto defrost function
- CFC-free refrigerant and energy-saving
- Equipped with thermal printer

Applications

- Used to store blood, research laboratories, clinical research laboratories and in pathological testing.

Standard Accessories

- Caster
- Test hole

Optional Accessories

- Datalogger

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.
Email: info@labdex.com | Website: www.labdex.com